

Artshield™

Matte

Artshield™ Matte™ is a 3 mil (75μ) UV stabilized, pre-perforated clear PVC laminating film with a matte finish, coated on one side with a pH neutral heat activated solvent acrylic adhesive that is protected by a moisture stable bleached Kraft gridded release paper coated on one side with siliconized PE.

- THE FILM'S SOFT, NON-REFLECTIVE FINISH MAKES IT IDEAL FOR DIRECT GRAPHICS
- WHEN USED ON INKJET IMAGES FOR DISPLAYS, IT WILL CUT GLARE WITHOUT SACRIFICING COLOR DETAIL
- IDEAL FOR PLAQUES

PROCESS SETTINGS

Equipment Type & Temperature Speed

Roller Laminator
Not Recommended

Press
185°F to 210°F 2-6 minutes
(85°C to 99°C)

For more information,
performance and warranty guide
lines please contact your local
Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Perforated PVC
Adhesive	pH neutral Solvent Acrylic (Heat Activated)
Release Liner	1 Side PE Coated Bleached Kraft Grid Paper (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	3 mil (75μ) 4 mil (100μ)
Adhesive Layer	1 mil (25μ)
Film/Adhesive Ratio	3:1
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	Not Applicable
Peel Strength (20 min, FTM1)	18 N/25mm
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	1 Year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401 B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com