

Dynamic Plus

Lustre

Dynamic Plus Lustre is a 3.2 mil (80µ) monomeric soft calendared PVC laminating film with a lustre finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- LOW SHEEN WITHOUT LOSS OF CONTRAST OR SHARPNESS MAKES DYNAMIC PLUS LUSTRE EFFECTIVE FOR A WIDE RANGE OF APPLICATIONS
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS AND EVENT SIGNAGE.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Lustre Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ) 4.2 mil
Adhesive Layer	1 mil (25µ) (105µ)
Film/Adhesive Ratio	3.2:1
UV Protection	Yes
Outdoor Durability	3 Years
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC[®]
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com