

MHL™ Standard Temperature Matte is a 1.7 mil (43µ) high clarity, abrasion-resistant PET thermal laminating film designed for high-speed single- or double-sided lamination. The film is resistant to water, oil, acid, and alkali and can be die cut.

- IDEAL FOR LAMINATING BOOK JACKETS, POSTERS, MENUS, AND MAPS
- RECOMMENDED FOR APPLICATIONS THAT REQUIRE EXCELLENT CLARITY AND PROTECTION

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	1.7 mil (43µ)
<b>Film/Adhesive Ratio</b>	0.5:1.2
<b>Processing Temperature</b>	210°F to 230°F (99°C to 110°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

**DRYTAC**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013