

Polar®

Dynamic Clear Gloss R

Polar® Dynamic Clear Gloss R provides an excellent printing surface. Polar® Dynamic Clear Gloss R also offers excellent indoor and outdoor durability with a 3 year lifespan for exterior applications. With a removable adhesive, Polar® Dynamic Clear Gloss R maximizes adhesive performance on a wide variety of substrates, especially glass and other smooth surfaces.

- PHTHALATE-FREE PRODUCT
- REMOVES CLEANLY
- CLEAR FILM WITH CLEAR ADHESIVE

3.7
mil

Clear
Monomeric
PVC



Gloss



(Eco) Solvent
Latex
UV



Clear
Removable
Acrylic (Pressure Sensitive)



Widths up to 54 in



EXTERIOR & INTERIOR

HIGH QUALITY CLEAR FILM WITH CLEAR ADHESIVE



APPLICATIONS

POP AND ADVERTISING
GRAPHICS
POSTERS
EXHIBITION GRAPHICS
GENERAL SIGNAGE
CONSTRUCTION BARRICADES



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar®

Dynamic Clear Gloss R

Polar® Dynamic Clear Gloss R is a 3.7 mil (94µ) clear monomeric PVC film with a gloss finish. Polar® Dynamic Clear Gloss R is coated with a clear removable, pressure sensitive acrylic adhesive that is protected by a 78# PE Coated Kraft release liner. The high quality film of Polar® Dynamic Clear Gloss R provides a consistent printing surface. The removable adhesive allows for optimum adhesive performance on a wide variety of substrates, especially windows.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. It is recommended a heat gun be used if removing in colder temperatures (41°F/ 5°C).

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Gloss Clear Monomeric PVC
Adhesive	Removable Clear Acrylic (Pressure Sensitive)
Release Liner	78# Poly Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.7 mil (94µ) 4.7 mil
Adhesive Layer	1 mil (25µ) (119µ)
Outdoor Durability	3 Years; Ink Dependent
Application Temperature	>-5°F (-20°C)
Service Temperature Range	-5°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Dynamic Clear Gloss R, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Polymeric are Drytac's Dynamic™ Plus overlaminates.

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com