

# ReTac®

## Duo

ReTac® Duo is a 1 mil (25µ) clear PET film, coated on both sides with adhesive. It has a permanent adhesive on one side to be used on graphic prints and ReTac® ultra removable adhesive on the other, allowing it to be easily removed and re-positioned for repeated use. ReTac® Duo is designed to adhere to walls, doors or any smooth surface without leaving behind residue or damaging the surface when removed. The adhesive is self-wound on a two-sided, PE coated siliconized Kraft release paper.

- IDEAL FOR TRANSFORMING PHOTOS, POSTERS, GRAPHICS, OR NEWS CLIPPINGS INTO WALL OR WINDOW GRAPHICS OR RE-POSITIONABLE DECALS

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2019 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Adhesive</b>	Permanent Acrylic (Pressure Sensitive)
<b>Film</b>	Clear PET
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive
<b>Release Liner</b>	2 Side PE Coated, 2 Side Siliconized Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	1 mil (25µ)	3 mil (75µ)
<b>Adhesive Layer</b>	1 mil (25µ) on each side	
<b>Outdoor Durability</b>	2 Years	
<b>Application Temperature</b>	41°F (5°C)	
<b>Service Temperature Range</b>	40°F to 120°F (4.4°C to 48.9°C)	
<b>Shelf Life</b>	2 Years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013