

Polar®

Choice Air White

Polar® Choice Air White is the ideal choice for an easy to apply, bubble-free, printable monomeric PVC film. Available with a gloss finish and a permanent adhesive, Polar® Choice Air White maximises adhesive performance on a wide variety of substrates.

Polar® Choice Air White is outdoor durable for up to 5 years and is ideal for signage and general advertising applications, including windows, POP displays, stickers and decals.

- BUBBLE-FREE, AIR RELEASE LINER TECHNOLOGY
- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- SUITABLE FOR MANY APPLICATIONS

Product Code: **CGAG**

80
micron

White
Monomeric
PVC


Gloss



(Eco)Solvent
Latex
UV



Grey Permanent
Acrylic Solvent
Adhesive



Widths up to 1524mm



5 YEARS
INTERIOR & EXTERIOR
(unprinted)

EASY TO APPLY MONOMERIC PVC



APPLICATIONS

GENERAL SIGNAGE
WINDOW GRAPHICS
EXHIBITION GRAPHICS
POS DISPLAY



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Polar®

Choice Air White Gloss PB

Polar® Choice Air White Gloss PB is an 80µ (3.2 mil) gloss white monomeric PVC film, coated on one side with a permanent, pressure sensitive grey solvent acrylic adhesive that is protected by a 140gsm embossed white 2 side PE coated release liner with bubble free technology. Suitable for interior and exterior use (up to 5 years).

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Gloss Monomeric PVC
Adhesive	Grey Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	140gsm Embossed White 2 side PE Coated Release Paper (Bubble Free)

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ) 4.2 mil (105µ)
Adhesive Layer	1 mil (25µ) (105µ)
Outdoor Durability	5 Years (Unprinted)
Fire Rating (EN 13501-1)	Class B
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Choice, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Choice are Drytac's Dynamic™, Interlam™ or Protac™ overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com