

Interlam™ Eco

Anti-Graffiti

Interlam Eco Anti-Graffiti is a 1.0 mil (25µ) clear PET laminating film with strong anti-stick and anti-graffiti characteristics, that is coated with a pressure sensitive acrylic adhesive and protected by a siliconized PE coated paper release liner. The film is resistant to dirt and pollutants, and the gloss finish offers superb clarity, detail and color contrast. The anti-stick properties of the film inhibit adhesion of any adhesives, tapes or media. It wipes clean of virtually any spray paint and can be scraped off without adverse effects.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE ON FLEXIBLE MEDIA SUBSTRATES WHERE AN ANTI-GRAFFITI/ANTI-STICK FILM IS REQUIRED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film	Gloss Polyester (PET)
Adhesive	Permanent Acrylic (Pressure Sensitive)
Release Liner	50# Siliconized Kraft

PRODUCT CHARACTERISTICS

Film Thickness	1.0 mil (25µ)	2.2 mil (55µ)
Adhesive Layer	1.2 mil (30µ)	
Outdoor Durability	3 Years	
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)	
Application Temperature	-4°F (-20°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013