

# HT Ultra

## High Tack Ultra

EXCELLENT PRINTING SURFACE

HT ultra is a 4 mil (100µ) white monomeric self-adhesive PVC film with a high tack clear permanent adhesive that is protected by a 135gsm, 1 side siliconised white clay coated kraft liner. HT Ultra was designed for applications requiring a strong initial grab and subsequent bond on a variety of different surfaces including steel, glass, plastic, wood, and more.

- IDEAL FOR PERMANENT APPLICATIONS SUCH AS MACHINERY LABELS AND EQUIPMENT STICKERS.
- PROVIDES A STRONG BOND TO MOST FLAT SURFACES.
- SUITABLE FOR UNLIMITED INDOOR USE & SHORT TO MEDIUM TERM OUTDOOR USE.

100  
micron

White  
Monomeric  
PVC

Matte or  
Gloss



(Eco)Solvent  
Latex  
UV



Clear High-Tack  
Acrylic Adhesive



Widths up to 1370mm



3 YEARS DURABILITY  
INTERIOR & EXTERIOR\*



### APPLICATIONS

- Decals & Stickers
- Machinery Labels
- Wayfinding Signage
- Asset Tagging



# DRYTAC<sup>®</sup>

ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# HT Ultra

## TECHNICAL SPECIFICATION

HT ultra is a 4 mil (100µ) white monomeric self-adhesive PVC film with a high tack clear permanent adhesive that is protected by a 135gsm, 1 side siliconised white clay coated kraft liner. HT Ultra was designed for applications requiring a strong initial grab and subsequent bond on a variety of different surfaces including steel, glass, plastic, wood, and more.

- IDEAL FOR PERMANENT APPLICATIONS SUCH AS MACHINERY LABELS AND EQUIPMENT STICKERS.
- PROVIDES A STRONG BOND TO MOST FLAT SURFACES.
- SUITABLE FOR UNLIMITED INDOOR USE & SHORT TO MEDIUM TERM OUTDOOR USE.

### INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Wet application is not recommended.

### PRODUCT STRUCTURE

<b>Film</b>	White Matte or Gloss Monomeric PVC
<b>Adhesive</b>	High Tack Clear Acrylic (Pressure Sensitive)
<b>Release Liner</b>	135gsm 1 Side Siliconised White Clay Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	4 mil (100µ)   4.2 mil (105µ)
<b>Adhesive Layer</b>	1 mil (25µ)   (105µ)
<b>Outdoor Durability</b>	3 Years (Unprinted)
<b>Fire Rating (EN 13501-1)</b>	Class B
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity

### OVERLAMINATE RECOMMENDATIONS

When using HT Ultra, an overlamine can be used for maximum life expectancy. Products recommended for use with HT Ultra are Drytac's Interlam™ products.

**DRYTAC**<sup>®</sup>  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013