

# Polar<sup>®</sup>

## Frost Air

Polar<sup>®</sup> Frost Air is a premium translucent matte polymeric film with a subtle embossed finish that simulates the elegant look of etched glass at a more affordable price.

It offers easy, bubble-free application with its air egress technology, requiring no water or messy application processes.

Ideal for high-end office spaces, interior décor, retail displays, and more, Polar<sup>®</sup> Frost Air delivers a professional, frosted glass effect that enhances any environment while maintaining a simple, clean installation process.

- CAN BE USED PRINTED OR UNPRINTED
- EASY, BUBBLE FREE APPLICATION
- DRY INSTALLATION - NO WATER NEEDED

**Product Code: PPFA**

**90  
micron**

Translucent  
Embossed  
Polymeric



Matte



(Eco) Solvent  
Latex  
UV



Clear  
Permanent  
with Bubble Free Technology



Widths up to 1520mm



**INTERIOR & EXTERIOR**

## ELEGANT ETCHED GLASS EFFECT



## APPLICATIONS

Indoor/Exterior Graphics  
Office Environments  
Retail Branding  
Trade Shows

**DRYTAC<sup>®</sup>**  
**ADHESIVE SCIENCE**

[www.drytac.com](http://www.drytac.com)



## Frost Air

Polar® Frost Air is a 3.6mil (90µ) high quality, translucent matte polymeric PVC film with an embossed pearl finish. It is coated with a clear permanent adhesive that is protected by a two-sided PE coated release liner with bubble-free technology.

Polar® Frost Air is compatible with Eco (Solvent), Latex, and UV print technologies, making it the ideal solution for custom window graphics for interior decor, office environments, retail branding solutions, trade shows, and more.

- IDEAL FOR INTERIOR & EXTERIOR BRANDING
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- IDEAL FOR PRIVACY FILMS IN OFFICE ENVIRONMENTS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Translucent Matte Polymeric PVC
Adhesive	Clear Permanent
Release Liner	2 Sided PE Coated with Bubble-Free Technology

### PRODUCT CHARACTERISTICS

Film Thickness	3.6 mil (90µ)
Outdoor Durability	5 Years (unprinted)
Application Temperature	>50°F (10°C)
Service Temperature Range	-49°F to 179.6°F (-45°C to 82°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)