

Polar[®]

Frost

Polar[®] Frost is a premium translucent matte polymeric film with a subtle embossed finish that simulates the elegant look of etched glass at a more affordable price.

It is recommended to apply Polar Frost using a wet installation method to ensure a clean, bubble-free finish and optimal adhesion.

Ideal for high-end office spaces, interior décor, retail displays, and more, Polar[®] Frost delivers a professional, frosted glass effect that enhances any environment while maintaining a simple, clean installation process.

- CAN BE USED PRINTED OR UNPRINTED
- IDEAL FOR PRIVACY, DÉCOR, AND BRANDING ON WINDOWS AND GLASS PARTITIONS
- TRADITIONAL WET INSTALLATION IS RECOMMENDED

Product Code: PF

3.6
mil Translucent
Embossed
Polymeric



Matte



(Eco) Solvent
Latex/Resin
UV



Clear
Permanent



Widths up to 60 in



5 YEARS DURABILITY
INTERIOR AND EXTERIOR

ELEGANT ETCHED GLASS EFFECT



APPLICATIONS

Indoor/Exterior Graphics
Office Environments
Retail Branding
Hospitality Spaces

DRYTAC[®]
ADHESIVE SCIENCE

www.drytac.com

Polar[®] Frost is a 3.6mil (90µ) high quality, translucent matte polymeric PVC film with an embossed pearl finish. It is coated with a clear permanent adhesive that is protected by a two-sided PE coated release liner.

Polar[®] Frost is compatible with Eco (Solvent), Latex/Resin, and UV print technologies, making it the ideal solution for custom window graphics for interior decor, office environments, retail branding solutions, trade shows, and more.

- IDEAL FOR INTERIOR & EXTERIOR BRANDING
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- IDEAL FOR PRIVACY FILMS IN OFFICE ENVIRONMENTS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Translucent Matte Polymeric PVC
Adhesive	Clear Permanent
Release Liner	2 Sided PE Coated

PRODUCT CHARACTERISTICS

Film Thickness	3.6 mil (90µ)
Total Light Transmittance	56%
Haze	75%
Adhesive Layer	1.0 mil (25µ)
Outdoor Durability	5 Years (unprinted)
Application Temperature	>50°F (10°C)
Service Temperature Range	-49°F to 179.6°F (-45°C to 82°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013