

# Polar<sup>®</sup>

## Frost


Polar<sup>®</sup> Frost is a premium translucent matte polymeric film with a subtle embossed finish that simulates the elegant look of etched glass at a more affordable price.


It is recommended to apply Polar Frost using a wet installation method to ensure a clean, bubble-free finish and optimal adhesion.

Ideal for high-end office spaces, interior décor, retail displays, and more, Polar<sup>®</sup> Frost delivers a professional, frosted glass effect that enhances any environment while maintaining a simple, clean installation process.


- CAN BE USED PRINTED OR UNPRINTED
- IDEAL FOR PRIVACY, DÉCOR, AND BRANDING ON WINDOWS AND GLASS PARTITIONS
- TRADITIONAL WET INSTALLATION IS RECOMMENDED

**Product Code: PF**

**90 micron** Translucent Embossed Polymeric  Matte

 (Eco) Solvent Latex/Resin UV

 Clear Permanent

 Widths up to 1520mm

 **5** YEARS DURABILITY **INTERIOR & EXTERIOR**

## ELEGANT ETCHED GLASS EFFECT



## APPLICATIONS

Indoor/Exterior Graphics  
Office Environments  
Retail Branding  
Hospitality Spaces

**DRYTAC<sup>®</sup>**  
**ADHESIVE SCIENCE**

[www.drytac.com](http://www.drytac.com)

# Polar<sup>®</sup>

## Frost

Polar<sup>®</sup> Frost is a 3.6mil (90µ) high quality, translucent matte polymeric PVC film with an embossed pearl finish. It is coated with a clear permanent adhesive that is protected by a two-sided PE coated release liner.

Polar<sup>®</sup> Frost is compatible with Eco (Solvent), Latex/Resin, and UV print technologies, making it the ideal solution for custom window graphics for interior decor, office environments, retail branding solutions, trade shows, and more.

- IDEAL FOR INTERIOR & EXTERIOR BRANDING
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- IDEAL FOR PRIVACY FILMS IN OFFICE ENVIRONMENTS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Translucent Matte Polymeric PVC
<b>Adhesive</b>	Clear Permanent
<b>Release Liner</b>	2 Sided PE Coated

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3.6 mil (90µ)
<b>Total Light Transmittance</b>	56%
<b>Haze</b>	75%
<b>Adhesive Layer</b>	1.0 mil (25µ)
<b>Outdoor Durability</b>	5 Years (unprinted)
<b>Application Temperature</b>	>50°F (10°C)
<b>Service Temperature Range</b>	-49°F to 179.6°F (-45°C to 82°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

# DRYTAC<sup>®</sup>

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013